

StOrge EleCtriC Water Heater

GUANGDONG WULIN FENG

StOrge EleCtriC Water Heater



HT01

Capacity: 30/40/50/60/80/100L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2200W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ380, 80/100L=Φ450



HT02

Capacity: 30/40/50/60/80/100L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2200W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ380, 80/100L=Φ450



HT03

Capacity: 30/40/50/60/80/100L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2200W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ380, 80/100L=Φ450



HT05

Capacity: 30/40/50/60/80/100L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2200W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ380, 80/100L=Φ450



HT06

Capacity: 30/40/50/60/80/100L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2200W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ380, 80/100L=Φ450



HB05



GUANGDONG WULIN FENG / StOrge EleCtriC Water Heater



HJ01

Capacity: 30/40/50/60/80/100L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2200W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ380, 80/100L=Φ450



HJ02

Capacity: 30/40/50/60/80/100L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2200W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ380, 80/100L=Φ450



HJ03

Capacity: 30/40/50/60/80/100L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2200W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ380, 80/100L=Φ450



HJ05

Capacity: 30/40/50/60/80/100L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2200W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ380, 80/100L=Φ450



HJ06

Capacity: 30/40/50/60/80/100L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2200W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ380, 80/100L=Φ450



HJ07

Capacity: 30/40/50/60/80/100L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2200W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ380, 80/100L=Φ450



TY01

Capacity: 30/40/50/60/80L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2000W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ380, 80L=Φ420



TY02

Capacity: 30/40/50/60/80L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2000W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ380, 80L=Φ420



PYS-01

Capacity: 30/40/50/60/80L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2000W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C
Product Size (mm): 30/60L=Φ340, 80L=Φ410



B201

Capacity: 40/50/60/80L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2000W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C



BG01

Capacity: 40/50/60/80L
Rated Voltage: 220V-240V ~
Rated Frequency: 50Hz/60Hz
Rated Power: 1500W/2000W
Rstd Pressure: 0.75MPa
Hot Wster temp.Limit: 75±5°C

